

# Headquarter:

No.60, Chuangyejie road, Suzhou, 215000, China 86 512 6631 5208 ce@celotech.com

## Technical Center:

B205, No.60, Chuangyejie road, Suzhou, China 215000 wp@celotech.com

## **Customer Service:**

ce@celotech.com export@celotech.com 86 512 66315208

## Website:

www.celotech.com







# CELOPRO® Hydroxy Ethyl Cellulose For Coatings Industry







# CELOPRO® Hydroxy Ethyl Cellulose For Coatings Industry

## Overview

Celopro® belongs to the group of additives with a broad range of applications. In coatings industry, Celopro® is mainly used in paints, normally water based paints for ceilings, walls and facades, but also in paste-like systems and other applications.

# Properties of Celopro® HHB

Due to its numerous properties, Celopro® is an important component in coating materials like water based paints and paste-like systems. The following properties of Celopro® are essential for the optimization of coatings.

- Biostable
- Consistency for application
- Water retention
- Binding power
- Function as a protective colloid

# Packaging and storage

Celopro® is packed in multi-layered paper bags with an inner polyethylene bag. Net weight: 25kg per bag.



Celopro® Hydroxyethylcellulose (HEC)
has long been recognized as an outstanding
thickener for both interior and exterior latex paints.
The major advantages are:

- Water soluble
- High thickening efficiency
- Compatibility with a broad range of paint ingredients
- Good brush and roller application
- Anti-sagging properties

## Specification & Applications

Product	Viscosity Range mPas		Interior paints	Exterior paints	Solid Piants	Silicone resin paints	Silicate paint	limewash paints	Cement paints
	1%	2%							
Celopro® HHB30S	1500-2400		•				•	0	0
Celopro® HHB50S	2400-3300		•	•	•	•	•	0	0
Celopro® HHB70S	3300-5600		•	0	•	•	0	0	0
Celopro® HHB300S		150-400	•	0	0	0	0	0	0
Celopro® HHB2000S		1500-2500	•	0	0	0	0	0	0
Celopro® HHB6000S		4500-6500		0	0	0	0	0	0